

# WK LED UNDERWATER LIGHTS

Available in Stainless Steel 304 and 316

## Recessed Underwater Light



- ① Stainless steel trim
- ② Stainless steel trim
- ③ Hi-power LED
- ④ Aluminium Circuit Board
- ⑤ 5mm tempered glass
- ⑥ Brass Cable gland



Plastic sleeve (optional)

### FEATURES

RoHS compliant materials  
 Optimum thermal management for Max. LED lifetime.  
 Opto LED symbiosis for peak lm  
 Option : DNX 512 compatible

Model	Light Source	Beam Angle(°)	Consumption(w)	IP Rating	Weight(kg)	Input Voltage
KL-4X0101	3×1W	25/45	3.5	68	2.33	24V DC
KL-4X0102	3×3W	25/45	8	68	2.33	24V DC
KL-4X0103	3×1W RGB	25/45	3.5	68	2.33	24V DC
KL-4X0104	3×3W RGB	25/45	8	68	2.33	24V DC
KL-4X0105	3×1.5W RGB 3IN1	25/45	4	68	2.33	24V DC
KL-4X0106	3×3W RGB 3IN1	25/45	8.2	68	2.33	24V DC

## Recessed Underwater Light



- ① Stainless steel trim
- ② Stainless steel trim
- ③ Hi-power LED
- ④ Aluminium Circuit Board
- ⑤ 5mm tempered glass
- ⑥ Brass Cable gland



Plastic sleeve (optional)

Model	Light Source	Beam Angle(°)	Consumption(w)	IP Rating	Weight(kg)	Input Voltage
KL-4Y0701	7×1W	25/45	8.2	68	2.33	24V DC
KL-4Y0702	7×3W	25/45	19.5	68	2.33	24V DC
KL-4Y0803	6×1W RGB	25/45	6.7	68	2.33	24V DC
KL-4Y0804	6×3W RGB	25/45	14	68	2.33	24V DC
KL-4Y0705	7×1.5W RGB 3IN1	45	10	68	2.33	24V DC
KL-4Y0706	7×3W RGB 3IN1	45	19.6	68	2.33	24V DC